

High Speed Hard Floor Care

daily procedures



Dust mop 1 or more times per day to remove surface soil.



Use scraper and gum remover to remove gum and other attached soil deposits.



Vacuum or shake out walk-off mats. Replace mats as needed. The more dirt you stop at the entrances, the longer the floor finish will last and maintain a higher appearance level.



Mix all purpose cleaner following label directions.



Fill automatic scrubber with all purpose solution.



Scrub area with an automatic equipped with red pads, using medium pad pressure, with feed valve 3/4 open, squeegee down and vacuum motor on.



Pick up trail with a clean mop and water.



If automatic is not available, liberally apply all purpose solution with mop.



Scrub with circular scrubber, equipped with a red pad.



Pick up solution with wet/dry vacuum or mop. Rinse using clean mop, changing water frequently.



Make sure floor is clean. If not, repeat above procedure.



Allow floor to dry.



Always make sure there is a sufficient finish base on the floor before buffing with a high-speed machine to avoid permanent tile damage.



Once floor is dry, walk in a straight line at normal pace with a high-speed machine.



Do not stop or allow machine to run in one spot.



When finished, dust mop entire area.



Clean and store all equipment for future use.



LEWIS COUNTY CHEMICAL

JANITORIAL AND PAPER PRODUCTS

Industrial . Healthcare . Education . Warewash
Hospitality . Commercial . Military
Building Maintenance